

ITP-Portable BT



MODEL	ITP-Portable BT
Printing	
Printing method	Direct thermal
Printing speed	70mm/sec
Printing width	79.5±0.5mm
Maximum paper diameter	50mm
Paper thickness	0.06-0.08mm
Column capacity	576 dots/line, 512 dots/line
Interface	USB+Bluetooth
Column number	
Character size	ANK, Font A: 1.5×3.0mm (12×24 dots), Font B: 1.1×2.1mm (9×17 dots), Chinese, traditional Chinese: 3.0×3.0mm (24×24 dots)
Barcode Character	
Extension character sheet	PC347 (Standard Europe), Katakana, PC850 (Multilingual), PC860 (Portuguese), PC863 (Canadian-French), PC865 (Nordic), West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866 (Cyrillic#2), PC852 (Latin2), PC858, IranII, Latvian, Arabic, PT151 (1251)
Barcode types	1D Barcode: UPC-A /UPC-E /JAN13(EAN13) /JAN8(EAN8) /CODABAR /ITF /CODE39 /CODE93 /CODE128 /2D Barcode: QR CODE/PDF417
Buffer	
Input buffer	32k bytes
NV Flash	64k bytes
Power	
Power supply	Input: AC 110V/240V, 50~60Hz
Power source	Output: DC 9V-2A
Battery	2000mAh
Physical characteristics	
Weight	0.325KG
Dimensions	136×116×60mm(DxWxH)
Environmental Requirements	
Work environment	Temperature (0~45) humidity(10~80%)
Storage environment	Temperature(-10~60°C) humidity(10~90%)
OS	
Operating system	Win XP/Win 7/Win 8/Win 10/Linux/IOS/Android
Reliability	
Printer head life	50Km
Warranty	
Warranty	2 years